

Overcoming Fake Solutions in Neural Optimal Transport: A Smoothing Approach for Learning the Optimal Transport Plan



2025 KIAS CAINS Workshop

JaeWoong Choi

(with Jaemoo Choi and Dohyun Kwon)

SKKU Statistics

CONTENTS


1. Introduction
2. Fake Solutions in Neural Optimal Transport
3. Proposed Method
4. Experiments

Introduction

Introduction

Optimal Transport (OT) Problem

- Optimal Transport refers to the most **cost-minimizing way to transport source distribution μ to target ν .**



[1] Villani, Cédric. *Optimal transport: old and new*. Vol. 338. Berlin: springer, 2009.

[2] Rout, Litu, Alexander Korotin, and Evgeny Burnaev. "Generative modeling with optimal transport maps." *ICLR*, 2022.

Introduction

Optimal Transport (OT) Problem


- Optimal Transport refers to the most **cost-minimizing way to transport source distribution μ to target ν** .

- Monge's Formulation.**

$$C(\mu, \nu) := \inf_{T_{\#}\mu=\nu} \left[\int_{\mathcal{X}} c(x, T(x)) d\mu(x) \right].$$

Transport Map T

$$x \sim \mu \Rightarrow T(x) \sim \nu$$



Monge's Optimal Transport [2]

[1] Villani, Cédric. *Optimal transport: old and new*. Vol. 338. Berlin: springer, 2009.

[2] Rout, Litu, Alexander Korotin, and Evgeny Burnaev. "Generative modeling with optimal transport maps." *ICLR*, 2022.

Introduction

Optimal Transport (OT) Problem


- Optimal Transport refers to the most **cost-minimizing way to transport source distribution μ to target ν** .

- Monge's Formulation.**

$$C(\mu, \nu) := \inf_{T_{\#}\mu=\nu} \left[\int_{\mathcal{X}} c(x, T(x)) d\mu(x) \right].$$

Transport Map T
 $x \sim \mu \Rightarrow T(x) \sim \nu$

Optimality by cost-minimizing



Monge's Optimal Transport [2]

[1] Villani, Cédric. *Optimal transport: old and new*. Vol. 338. Berlin: springer, 2009.

[2] Rout, Litu, Alexander Korotin, and Evgeny Burnaev. "Generative modeling with optimal transport maps." *ICLR*, 2022.


Introduction

Optimal Transport (OT) Problem

- Optimal Transport refers to the most **cost-minimizing way to transport source distribution μ to target ν** .

- Monge's Formulation.**

$$C(\mu, \nu) := \inf_{T \# \mu = \nu} \left[\int_{\mathcal{X}} c(x, T(x)) d\mu(x) \right].$$



Monge's Optimal Transport [2]

- Kantorovich's Relaxation.**

$$C(\mu, \nu) := \inf_{\pi \in \Pi(\mu, \nu)} \left[\int_{\mathcal{X} \times \mathcal{Y}} c(x, y) d\pi(x, y) \right].$$

where $\Pi(\mu, \nu) :=$ the set of joint probability distributions on $\mathcal{X} \times \mathcal{Y}$ whose marginals are μ and ν .


[1] Villani, Cédric. *Optimal transport: old and new*. Vol. 338. Berlin: springer, 2009.

[2] Rout, Litu, Alexander Korotin, and Evgeny Burnaev. "Generative modeling with optimal transport maps." *ICLR*, 2022.

Introduction

Neural Optimal Transport

- Today, we focus on approaches for **learning optimal transport maps with neural networks**.




[1] Villani, Cédric. *Optimal transport: old and new*. Vol. 338. Berlin: springer, 2009.

[2] Rout, Litu, Alexander Korotin, and Evgeny Burnaev. "Generative modeling with optimal transport maps." *ICLR*, 2022.

Fake Solutions in Neural OT

Optimal Transport Map (OTM)

- OTM [1, 2] learns the **transport map** T through a max-min formulation.
 - v^c denotes the **c-transform** of v , i.e., $v^c(x) = \inf_{y \in \mathcal{Y}} (c(x, y) - v(y))$.




Static Optimal Transport

$$\begin{aligned} C(\mu, \nu) &:= \inf_{\pi \in \Pi(\mu, \nu)} \left[\int_{\mathcal{X} \times \mathcal{Y}} c(x, y) d\pi(x, y) \right], \\ &\quad \downarrow \text{Semi-dual formulation for OT} \\ &= \sup_{v \in L^1(\nu)} \left[\int_{\mathcal{X}} \underbrace{v^c(x)}_{\text{c-transform of } v} d\mu(x) + \int_{\mathcal{Y}} v(y) d\nu(y) \right] \end{aligned}$$

Optimal Transport Map (OTM)

- OTM [1, 2] learns the **transport map** T through a max-min formulation.

- v^c denotes the **c-transform** of v , i.e., $v^c(x) = \inf_{y \in \mathcal{Y}} (c(x, y) - v(y))$.



Static Optimal Transport

$$C(\mu, \nu) := \inf_{\pi \in \Pi(\mu, \nu)} \left[\int_{\mathcal{X} \times \mathcal{Y}} c(x, y) d\pi(x, y) \right],$$

Semi-dual formulation for OT

$$= \sup_{v \in L^1(\nu)} \left[\int_{\mathcal{X}} \underbrace{v^c(x)}_{\text{c-transform of } v} d\mu(x) + \int_{\mathcal{Y}} v(y) d\nu(y) \right]$$

$$\rightarrow \mathcal{L}_{v_\phi, T_\theta} = \sup_{v_\phi} \left[\int_{\mathcal{X}} \inf_{T_\theta} [c(x, T_\theta(x)) - v_\phi(T_\theta(x))] d\mu(x) + \int_{\mathcal{Y}} v_\phi(y) d\nu(y) \right].$$

$$T_\theta : \mathcal{X} \rightarrow \mathcal{Y}, x \mapsto \arg \inf_{y \in \mathcal{Y}} [c(x, y) - v(y)]$$

Min-max objective between Transport map T and Potential v

Fake Solutions in Semi-dual Neural OT (SNOT)

- The semi-dual approach is known to have the **fake solutions**.

$$\sup_V \inf_{T: \mathcal{X} \rightarrow \mathcal{Y}} \mathcal{L}(V, T) \quad \text{where} \quad \mathcal{L}(V, T) := \int_{\mathcal{X}} c(x, T(x)) - V(T(x)) d\mu(x) + \int_{\mathcal{Y}} V(y) d\nu(y).$$

- When the optimal potential V^* and the transport map T^* exists, it is well known that [1, 2]

$$T^* \in \arg \min_T \mathcal{L}(V^*, T)$$

- Thus, the pair (V^*, T^*) is the solution to the max-min problem.

Fake Solutions in Semi-dual Neural OT (SNOT)

- The semi-dual approach is known to have the **fake solutions**.

$$\sup_V \inf_{T: \mathcal{X} \rightarrow \mathcal{Y}} \mathcal{L}(V, T) \quad \text{where} \quad \mathcal{L}(V, T) := \int_{\mathcal{X}} c(x, T(x)) - V(T(x)) d\mu(x) + \int_{\mathcal{Y}} V(y) d\nu(y).$$

- When the optimal potential V^* and the transport map T^* exists, it is well known that [1, 2]


$$T^* \in \arg \min_T \mathcal{L}(V^*, T)$$

- Thus, the pair (V^*, T^*) is the solution to the max-min problem.
- However, **not all solutions** of the max-min problem correspond to the **true optimal potential and transport map pair**.
- The optimal solution of SNOT framework may fail to recover the correct optimal transport map.

Fake Solution Example

- Assume that the **source** μ and **target** ν distributions are **uniformly supported** on

$$A = [-1, 1] \times \{0\} \quad \text{and} \quad B = \{0\} \times [-1, 1].$$



Fake Solutions in Semi-dual Neural OT

Fake Solution Example


- Assume that the **source** μ and **target** ν distributions are **uniformly supported** on

$$A = [-1, 1] \times \{0\} \quad \text{and} \quad B = \{0\} \times [-1, 1]$$

- All transport map achieves the **same transport cost**:

$$\int_{\mathcal{X}} c(x, T(x)) d\mu(x) = \frac{1}{2} \int_{-1}^1 x_1^2 d\mu(x) - \int_{\mathcal{X}} \langle x, T(x) \rangle d\mu(x) + \frac{1}{2} \int_{-1}^1 y_1^2 d\nu(y) = \frac{2}{3}.$$

- Since all transport maps yield the same cost, **any transport map becomes an OT Map T^*** .



Fake Solution Example

- To analyze the fake solution, we first show that V^* is the optimal Kantorovich potential

$$V^*(y) = \frac{1}{2} \|y\|^2.$$

Dual Prob

$$S(\mu, \nu) := \sup_{V \in \mathcal{S}_c} \left[\int_{\mathcal{X}} V^c(x) d\mu(x) + \int_{\mathcal{Y}} V(y) d\nu(y) \right]$$

Fake Solutions in Semi-dual Neural OT

Fake Solution Example

- To analyze the fake solution, we first show that V^* is the optimal Kantorovich potential

$$V^*(y) = \frac{1}{2} \|y\|^2.$$

- This result follows from solving the **inner problem** of SNOT (dual OT problem) as follows:

$$\sup_V \inf_{T: \mathcal{X} \rightarrow \mathcal{Y}} \mathcal{L}(V, T) \quad \text{where} \quad \mathcal{L}(V, T) := \int_{\mathcal{X}} c(x, T(x)) - V(T(x)) d\mu(x) + \int_{\mathcal{Y}} V(y) d\nu(y).$$

$$\inf_T \int_{\mathcal{X}} \frac{1}{2} \|x\|^2 - \langle x, T(x) \rangle d\mu(x) + \int_{\mathcal{Y}} \frac{1}{2} \|y\|^2 d\nu(y) = \frac{2}{3}.$$

where the cost function is the quadratic cost $c(x, y) = \frac{1}{2} \|x - y\|^2$.

- Since V^* achieves the optimal transport cost, V^* is the **Kantorovich potential**.

Fake Solution Example

- The max-min solution of the SNOT problem is defined as the **minimizer of inner problem**.
- This implies that **any measurable map $T_\theta: A \rightarrow B$** can be a max-min solution of SNOT.

$$T_\theta : x \mapsto \arg \min_{y \in \mathcal{Y}} [c(x, y) - V_\phi(y)]$$

$$\inf_T \int_{\mathcal{X}} \frac{1}{2} \|x\|^2 - \langle x, T(x) \rangle d\mu(x) + \int_{\mathcal{Y}} \frac{1}{2} \|y\|^2 d\nu(y) = \frac{2}{3}.$$

No dependency on T

Fake Solutions in Semi-dual Neural OT

Fake Solution Example

- The max-min solution of the SNOT problem is defined as the **minimizer of inner problem**.
- This implies that **any measurable map $T_\theta: A \rightarrow B$** can be a max-min solution of SNOT.


$$T_\theta : x \mapsto \arg \min_{y \in \mathcal{Y}} [c(x, y) - V_\phi(y)]$$

$$\inf_T \int_{\mathcal{X}} \frac{1}{2} \|x\|^2 - \langle x, T(x) \rangle d\mu(x) + \int_{\mathcal{Y}} \frac{1}{2} \|y\|^2 d\nu(y) = \frac{2}{3}.$$

No dependency on T

- There is no **constraint ensuring that $T_\theta \mu = \nu$** .

Fake Solution Visualization



Sufficient Conditions for Ensuring True Solution

- The max-min solution (V^\dagger, T^\dagger) and the optimal solution (V^*, T^*) satisfy:

$$\{(V^*, T^*)\} \subsetneq \{(V^\dagger, T^\dagger)\}.$$

- The sufficient condition to prevent fake solution is as follows:

Theorem 3.1. Let $\mu \in \mathcal{P}_2(\mathcal{X})$, $\nu \in \mathcal{P}_2(\mathcal{Y})$, and $c(x, y) = \frac{1}{2}\|x - y\|^2$. Assume that μ does not give mass to the measurable sets of Hausdorff dimension at most $d - 1$ dimension.

(1) Then, there exists a unique OT Map T^* in (Eq. 3) and the Kantorovich potential $V^* \in S_c$ in (Eq. 5).

(2) For the Kantorovich potential $V^* \in S_c$, the minimization problem,

$$\mathcal{D}_x := \arg \min_{y \in \mathcal{Y}} [c(x, y) - V^*(y)], \quad (10)$$

is uniquely determined μ -a.s., i.e. $\mathcal{D}_x = \{y_x\}$ for μ -a.s $x \in \mathcal{X}$. In particular, a map $x \mapsto y_x \in \mathcal{D}_x$ is a unique OT Map T^* in law.

Condition on μ
Ex) Absolutely continuous

T_θ -parametrization

Sufficient Conditions for Unique max-min Solution

- The max-min solution (V^\dagger, T^\dagger) and the optimal solution (V^*, T^*) satisfy:

$$\{(V^*, T^*)\} \subset \{(V^\dagger, T^\dagger)\} \quad \text{Unique}$$

- For completeness, an additional condition for ν is required to ensure **the uniqueness of the mix-min solution**.

Corollary 3.3. *Suppose $\mathcal{Y} \subset \mathbb{R}^d$ is a closure of a bounded open set. Suppose $\mu \in \mathcal{P}_2(\mathcal{X})$ and $\nu \in \mathcal{P}_2(\mathcal{Y})$ are absolutely continuous distributions that have positive density functions on their domain. Then, the solution (V^*, T^*) of equation (9) is unique. In other words, $V^* \in S_c$ is unique up to constant, and T^* is a deterministic OT Map.*


Failure Cases When Our Conditions Is Not Met

When only Stochastic Transport π^* exists

- Assume that the **source** μ and **target** ν distributions are uniformly supported on

$$A = [0, 1] \times \{0\} \quad \text{and} \quad B = [0, 1] \times \{1\} \cup [0, 1] \times \{-1\}.$$

- The **standard SNOT** parameterizes the transport map with as **deterministic function** T_θ .
 - When only an OT Plan π^* exists, the SNOT cannot accurately represent the stochastic OT Map.




Failure Cases When Our Conditions Is Not Met

When only Stochastic Transport π^* exists

- Any function $T(x) = T_1(x)$ or $T_2(x)$ becomes a max-min solution of SNOT.

$$T_1(x) = (x_1, 1) \quad \text{and} \quad T_2(x) = (x_1, -1).$$

Fake Solution Visualization



Failure Cases When Our Conditions Is Not Met

When only Stochastic Transport π^* exists

- The **naïve stochastic parametrization** of OT Map **cannot address this problem**.
 - Given a stochastic variable $z \sim N(0, I)$, the stochastic parametrization is given as:

$$T_\theta(x, z) \in \arg \min_{y \in \mathcal{Y}} \{c(x, y) - V^\star(y)\}$$

Failure Cases When Our Conditions Is Not Met

When only Stochastic Transport π^* exists

- The **naïve stochastic parametrization** of OT Map **cannot address this problem**.

- Given a stochastic variable $z \sim N(0, I)$, the stochastic parametrization is given as:

$$T_\theta(x, z) \in \arg \min_{y \in \mathcal{Y}} \{c(x, y) - V^*(y)\}$$

- However, even stochastic parametrization does not guarantee the true solution.
 - It only ensures that the **transport plan π^\dagger is supported on the subdifferential**, i.e., $\pi^\dagger(\partial_c V^*) = 1$.

Proposition 3.4 (Informal). *Assume that the stochastic parametrization of $T_\theta(x, z)$ is ideally trained as in equation (17) for (μ, \mathcal{N}) -a.s. \mathcal{D}_x in Eq. 10 may not uniquely determined and $T_\theta(x, z)$ may contain fake solutions.*

Failure Cases When Our Conditions Is Not Met

Failure Cases Visualization




Figure 1. **Visualization of failure cases** by comparing the Optimal Transport map (**1st row**) and the max-min solution (**2nd row**) of Semi-dual Neural OT in the failure cases. The source data $x \sim \mu$, target data $y \sim \nu$, and generated data $T(x)$ are represented in Blue, Orange, and Red. The max-min solution fails to recover the correct OT Map.

Optimal Transport Plan (OTP) Model

Optimal Transport Plan (OTP)


Proposed Method

- Our goal is to learn the **OT Plan π^*** between the source distribution μ and the target distribution ν .

$$C(\mu, \nu) := \inf_{\pi \in \Pi(\mu, \nu)} \left[\int_{\mathcal{X} \times \mathcal{Y}} c(x, y) d\pi(x, y) \right]$$

- Why the stochastic OT Plan?

- Thm 3.1 is the inherent property of μ .** When this condition is not satisfied, the existence of OT Map T^* is not guaranteed.



Optimal Transport Plan (OTP)

Proposed Method

- Our goal is to learn the **OT Plan π^*** between the source distribution μ and the target distribution ν .

$$C(\mu, \nu) := \inf_{\pi \in \Pi(\mu, \nu)} \left[\int_{\mathcal{X} \times \mathcal{Y}} c(x, y) d\pi(x, y) \right]$$

- Why the stochastic OT Plan?**
 - Thm 3.1 is the inherent property of μ .** When this condition is not satisfied, the existence of OT Map T^* is not guaranteed.
- Our method consists of two steps:**
 - Introduce the **smoothed version** of the source distribution μ_ϵ .
 - Gradually adjust μ_ϵ** back to the original source measure μ .

Optimal Transport Plan (OTP)

OTP Model

- We require **two conditions on the smoothed measure μ_ϵ** :
 - (c1) μ_ϵ does not give mass to the measurable sets of Hausdorff dim at most $d - 1$ dim.
 - (c2) μ_{ϵ_k} weakly converges to μ as $k \rightarrow \infty$.

→ *Allows the SNOT to recover the true OT Plan and ensures the convergence of the OT Plan.*
- **Two options for the smoothing distribution.**
 - Gaussian convolution $\mu_{\epsilon_k} = \mu * N(0, \epsilon_k I)$
 - Variance-preserving convolution $\mu_{\epsilon_k} = (\sqrt{1 - \epsilon_k} Id)_\# \mu * N(0, \epsilon_k I)$

with a predefined noise schedule $\epsilon_k \searrow 0$

 - For noise-level scheduling, we follow diffusion model [1].

Optimal Transport Plan (OTP)

OTP Model

- Our method consists of two steps:

1. Apply SNOT on the smoothed measure μ_ϵ

- For each level ϵ_k , the **max-min solution** of $\mathcal{L}_{V,T}^k$ **recovers the OT Map T^*** and the Kantorovich potential V^* .

$$\mathcal{L}_{V_\phi, T_\theta}^k = \sup_{V_\phi} \left[\int_{\mathcal{X}} \inf_{T_\theta} [c(x, T_\theta(x)) - V_\phi(T_\theta(x))] d\mu_{\epsilon_k}(x) + \int_{\mathcal{X}} V_\phi(y) d\nu(y) \right].$$

Optimal Transport Plan (OTP)

OTP Model

■ Our method consists of two steps:

1. Apply SNOT on the smoothed measure μ_ϵ

- For each level ϵ_k , the **max-min solution** of $\mathcal{L}_{V_\phi, T}^k$ **recovers the OT Map T^*** and the Kantorovich potential V^* .

$$\mathcal{L}_{V_\phi, T_\theta}^k = \sup_{V_\phi} \left[\int_{\mathcal{X}} \inf_{T_\theta} [c(x, T_\theta(x)) - V_\phi(T_\theta(x))] d\mu_{\epsilon_k}(x) + \int_{\mathcal{Y}} V_\phi(y) d\nu(y) \right].$$

2. Gradually adjust μ_ϵ back to the original source measure μ .

- As $k \rightarrow \infty$, i.e., $\epsilon_k \searrow 0$, the **OT Plan $\pi_k^* = (Id, T_k^*)_{\#} \mu_{\epsilon_k}$** **converges (up to a subsequence) to π^*** .

Theorem 4.1. *Let $\{\mu_{\epsilon_k}\}_{k \in \mathbb{N}}$ be a sequence absolutely continuous probability measures, and T_k^* be the OT map from μ_{ϵ_k} to μ . If μ_{ϵ_k} weakly converges to μ as $k \rightarrow \infty$, then $\pi_k^* = (Id, T_k^*)_{\#} \mu_{\epsilon_k}$ weakly converges to the OT plan π^* between μ and ν , along a subsequence. Consequently, π_k^* from our OTP model with either convolution above also weakly converges to π^* , along a subsequence.*

Training Algorithm

Algorithm 1 Training algorithm of OTP

Require: Source distribution μ and the target distribution ν ; OT Map network T_θ and potential network V_ϕ ; Total number of iteration K ; Number of inner-loop iterations K_T ; Decreasing sequence of noise levels $\{\epsilon_k\}_{k=1}^K$.

- 1: **for** $k = 0, 1, 2, \dots, K$ **do**
 - 2: Sample a batch $x \sim \mu, y \sim \nu, z \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$.
 - 3: $\tilde{x} \leftarrow x + \sqrt{\epsilon_k} z$ or $\tilde{x} \leftarrow \sqrt{1 - \epsilon_k} x + \sqrt{\epsilon_k} z$.
 - 4: Update ϕ to maximize $\mathcal{L}_\phi = -V_\phi(T_\theta(\tilde{x})) + V_\phi(y)$.
 - 5: **for** $j = 0, 1, \dots, K_T$ **do**
 - 6: Sample a batch $x \sim \mu, z \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$.
 - 7: $\tilde{x} \leftarrow x + \sqrt{\epsilon_k} z$ or $\tilde{x} \leftarrow \sqrt{1 - \epsilon_k} x + \sqrt{\epsilon_k} z$.
 - 8: $\mathcal{L}_\theta = c(\tilde{x}, T_\theta(\tilde{x})) - V_\phi(T_\theta(\tilde{x})) + V_\phi(y)$.
 - 9: Update θ to minimize \mathcal{L}_θ .
 - 10: **end for**
 - 11: **end for**
-

Experiments

Experiments

Optimal Transport Plan Evaluation

- Our model learns a more accurate optimal transport plan compared to previous methods.




Figure 3. **Qualitative comparison between OTM (1st row) and our model (2nd row) on failure cases in Sec 3.2.** The noised source sample \tilde{x} in Alg 1 is denoted in Green. While OTM falls into fake solutions and fails to generate the target distribution correctly, our OTP model successfully learns the OT Plan.

Optimal Transport Plan Evaluation

- We evaluate our model against **SNOT (OTM)** and the **SNOT with a stochastic generator (OTM-s)**.
 - Transport cost error $D_{cost} = |W_2^2(\mu, \nu) - \int \|T_\theta(x) - x\|^2 d\mu(x)|$
 - Target distribution error $D_{target} = W_2^2(T_{\theta\#}\mu, \nu)$
 - Our model outperforms particularly in **high-dimensional settings**.

Table 1. Quantitative comparison of numerical accuracy on synthetic datasets. Each model is evaluated using two metrics: transport cost error $D_{cost}(\downarrow)$ and target distribution error $D_{target}(\downarrow)$.

| Dimension | Model | Perpendicular | | One-to-Many | |
|-----------|-------|---------------|---------------|---------------|--------------|
| | | D_{cost} | D_{target} | D_{cost} | D_{target} |
| $d = 2$ | OTM | 0.038 | 0.0079 | 0.069 | 0.10 |
| | OTM-s | 0.0070 | 0.018 | 0.35 | 0.032 |
| | Ours | 0.019 | 0.0068 | 0.0022 | 0.11 |
| $d = 4$ | OTM | 0.043 | 0.039 | 0.10 | 73.23 |
| | OTM-s | 0.033 | 0.065 | 0.010 | 0.038 |
| | Ours | 0.089 | 0.0086 | 0.033 | 0.094 |
| $d = 16$ | OTM | 0.16 | 4.97 | 71.28 | 73.23 |
| | OTM-s | 0.061 | 4.85 | 97.49 | 99.57 |
| | Ours | 0.058 | 0.59 | 0.057 | 0.65 |
| $d = 64$ | OTM | 2.13 | 19.37 | 21.92 | 32.94 |
| | OTM-s | 2.74 | 18.79 | 0.20 | 12.21 |
| | Ours | 0.97 | 10.09 | 0.14 | 9.98 |

Experiments

Neural OT Evaluation on I2I Translation Tasks

- **Stochastic Transport Application (MNIST-to-CMNIST)**
 - The naïve stochastic generator fails to learn the stochastic map.






Figure 2. Example of a stochastic transport map (OT Plan) task, e.g., MNIST-to-CMNIST colorization.



(a) OTM-s (FID=62.4, LPIPS=0.36)



(b) Ours (FID=3.18, LPIPS=0.32)

Figure 4. Experimental results on a stochastic transport map application, i.e., MNIST-to-CMNIST translation.

Neural OT Evaluation on I2I Translation Tasks

Image-to-Image Translation Benchmark

- We assessed our model on several Image-to-Image (I2I) translation benchmarks.

Table 2. **Image-to-Image translation benchmark** results compared to existing Neural (Entropic) OT models † indicates the results conducted by ourselves. DSBM scores are taken from (Gushchin et al., 2024; De Bortoli et al., 2024).

| Data | Model | FID (↓) | LPIPS (↓) |
|--------------------------|---|-------------|-------------|
| Male-to-Female (64x64) | NOT (Korotin et al., 2023b) | 11.96 | - |
| | OTM [†] (Fan et al., 2022) | 6.42 | 0.16 |
| | DIOTM [†] (Choi et al., 2024a) | 4.48 | 0.20 |
| | OTP (Ours) | 4.75 | 0.20 |
| Wild-to-Cat (64x64) | DSBM (Shi et al., 2024) | 20+ | 0.59 |
| | OTM [†] (Fan et al., 2022) | 12.42 | 0.47 |
| | DIOTM [†] (Choi et al., 2024a) | 10.72 | 0.45 |
| | OTP (Ours) | 9.66 | 0.52 |
| Male-to-Female (128x128) | DSBM (Shi et al., 2024) | 37.8 | 0.25 |
| | ASBM (Gushchin et al., 2024) | 16.08 | - |
| | OTM [†] (Fan et al., 2022) | 7.55 | 0.21 |
| | DIOTM [†] (Choi et al., 2024a) | 7.40 | 0.25 |
| | OTP (Ours) | 6.38 | 0.27 |

Conclusion

- Neural Optimal Transport is a powerful framework for generative modeling and image-to-image translation, but existing methods often suffer from **fake solutions**.
- We identify a **sufficient condition** that guarantees the avoidance of such fake solutions in Semi-dual Neural OT.
- We propose the **Optimal Transport Plan (OTP) model**, which introduces smoothing on the source measure to enable more reliable and accurate transport plan learning.
- Our OTP model **successfully recovers the correct OT Plan** in failure cases where existing models fail.
- These advancements **enhance the reliability** of Neural OT, making it more effective for various machine learning applications.


Thank you!

Failure Cases When Our Conditions Is Not Met

When unique T^* exists

- The previous examples is the case when T^* exists but is not unique.
- Assume that the **source μ** and **target ν** distributions are uniformly supported on

Not Absolutely Continuous $A = [-1, 1] \times \{0\}$ and $B = [-1, 1] \times \{1\}$.



Failure Cases When Our Conditions Is Not Met

When unique T^* exists

- Here, the optimal potential V^* and the OT Map T^* are as follows:

$$V^*(y) = \frac{1}{2} \|y_2\|^2 \quad \text{for } y = (y_1, y_2) \quad \text{and} \quad T^*(x) = (x_1, 1) \quad \text{for } x = (x_1, x_2).$$

- Any function $T((x_1, x_2)) := (x_1, a)$ for any $a \in \mathbb{R}$ becomes a max-min solution of SNOT.**

$$T_\theta : x \mapsto \arg \min_{y \in \mathcal{Y}} [c(x, y) - V_\phi(y)]$$

$$\inf_T \int_{\mathcal{X}} \frac{1}{2} \|x_1 - T(x)_1\|^2 d\mu(x) + \int_{\mathcal{Y}} \frac{1}{2} \|y\|^2 d\nu(y) = \frac{1}{2}.$$

No dependency on the second component

Fake Solution Visualization

